



Restore

Restoration Cleaning Detergent

Restore is a new technology, solvent free restoration cleaner for the removal of ingrained soils, carbon, soot, fire residues and rubber on hard and semi-porous surfaces. Excellent cleaner for fire restoration and safety flooring. A highly concentrated multi-surface, heavy duty industrial cleaner for use on floors, walls, carpets, hard surfaces, porous surfaces and many other professional and disaster restoration applications. Restore contains a unique non-caustic, solvent-free formula designed to penetrate and lift carbon, soot, smoke, grease, rubber and deeply ingrained soils.

BENEFITS

- **Soil Suspension** – Restore employs grease cutting agents to break through resistant soiling and specialty polymer technology to suspend the soils for effective rinsing.
- **Tracked in Soils** – Smart chemistry breaks down and suspends fine clays and atmospheric soiling. This is of particular benefit in areas where red soils are present.
- **Ultra Concentrate** – Super concentrate formula which allows it to be diluted to economical dilution ratios whilst still providing high performance cleaning.
- **Safety First** – Low VOC profile which means no unwanted, unpleasant vapours. This is complimented by it's outstanding low toxicity and OH&S ratings. This formula also is phosphate free and does not contribute to the eutrophication of our waterways.

DIRECTIONS for USE

Always pre-test surface in an inconspicuous area before proceeding. Do not use on water sensitive fabrics, unsealed wood, aluminium or other delicate surfaces.

Dilutions:

- **Normal Soiling**
Dilute 10 to 20ml Restore per litre of warm water (1:100 to 1:50)
- **Heavy Soiling & Restoration**
Dilute 50ml per litre of warm water (1:20).
- **Ceiling Cleaning**
Add 50ml 446 Oxyboost Plus per 5 litres of 985 Restore solution. (Observe cautions below)
- **Pressure Washing**
Mix 1 part 985 Restore with 4 parts water and meter at desired setting.

Application:

1. Apply by sprayer, sponge or floor machine.
2. Allow 2 to 5 minutes contact time. For heavy soil, scrub if needed, then rinse surface thoroughly with clean water.
3. Carpets and fabrics should be extraction rinsed with Settler.
4. For ceilings, apply Restore solution by specialised spray equipment and observe all safety precautions. Wear suitable personal protective equipment and cover all sensitive furnishings.